



D4202-1 SPACER

NOTES:
1) MATERIAL: 6061-T4/-T42 ALUMINUM TUBING PER WW-T-700/6, AMS 4081, OR ASTM B210 / B221 / B241
REF DART SPEC M6061T4T0.500W.058
OR



6061-T6/-T62 ALUMINUM TUBING PER WW-T-700/6, QQ-A-200/8, QQ-A-225/8, AMS 4080 / 4082, OR ASTM B210 / B221 / B241
REF DART SPEC M6061T6T0.500W.058

HEAT TREAT TO -T4/-T42 CONDITION. MIN UTS = 30 KSI (60 HREW MIN)

2) FINISH: NONE

3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED

4) UNITS: INCHES UNLESS OTHERWISE NOTED

5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX

6) IDENTIFICATION: NONE

7) WEIGHT: 0.03 lbs

D	REVISED TYPO IN NOTE 1, REF PAR17-585	VS	17.11.28
C	6061-T4 WAS 6061-T6, 0.058 WAS 0.049	CP	11.12.13
B	0.049 WAS 0.058, REASON: FACILITATE MFG	MB	11.03.22
A	NEW ISSUE	CP	10.09.22
REV.	DESCRIPTION		
DESIGN	VS	DART AEROSPACE LTD	
DRAWN	VS	HAWKESBURY, ONTARIO, CANADA	
CHECKED	RF	DRAWING NO.	REV. D
MFG. APPR.	DD	D4202	SHEET 1 OF 1
APPROVED	HS	TITLE	SCALE
DE APPR.	DS	SPACER	NTS
DATE	17.11.28	COPYRIGHT © 2010 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

APPROVED

RELEASED

2019 JAN 29

ECN 1T-536